

1500mW 5.8g 32CH FPV Video Transmitter

Features

- 3S-6S wide range voltage input
- 32 CH, compatible with 5.8g receivers
- 1500MW, 3000m transmitting distance in open area
- Detachable moisture-proof ABS shell, more simple installation

Specification

- Transmitter power: 1500mW
- 3000 transmission distance in open area
- Input power: 3S-6S (7-28V)
- Antenna connection: RP-SMA Jack in transmitter unit, RP-SMA Plug in antenna
- Antenna gain: 3dBi
- Working current: 800MA/12V
- Working temperature: -10? ~ 85? (14F ~ 185F)
- Net weight: 36g(without shell); 46g(with shell)
- Size: 64*35*27MM(with shell)

Accessories

- 3dBi antenna x 1
- Ribbon cable x 1

FR	CH	CH							
		CH1	CH2	CH3	CH4	CH5	CH6	CH7	CH8
FR	FR1 (A)	5965M	5845M	5825M	5805M	5785M	5765M	5745M	5725M
	FR2 (B)	5733M	5752M	5771M	5790M	5809M	5828M	5847M	5866M
	FR3 (E)	5705M	5685M	5665M	5645M	5625M	5905M	5925M	5945M
	FR4 (F)	5740M	5760M	5780M	5800M	5820M	5840M	5860M	5880M

